

48BMOP3P

Indoor 3-port fiber optic wall box

DESCRIPTION

It is compatible with SC duplex and LC quad adapters. Its multiple cable input options provide it with broad cabling modularity. The box is equipped with 48BMOPSC and 48BMOPOB faceplates.



ADVANTAGES

- Integrated coiling system
- Multiple cable input options



CONSTRUCTION & TECHNICAL PERFORMANCE

Color	Signal White RAL 9003
Compatible optical connector	LC Quad, SC Duplex
Number of Optical Fibers	12
Number of Accepted Fibers	Jusqu'à 12 FO
Optical Connector Type	LC SC
Dimensions (W x D x h)	33.33 x 180 x 150 mm
Containing Material	ABS
Maximum Capacity Modularity	Boitier fixe - Pose murale
Gross Scanned Weight of the US (g/km)	0.23

ELECTRICAL CHARACTERISTICS

Optical Performance	Aucune
---------------------	--------

TRANSMISSION CHARACTERISTICS

Data Transmission Standard	EN 50173, ISO 11801 ED3, TIA 568-C3
----------------------------	-------------------------------------

MECHANICAL CHARACTERISTICS

Optical mounting type	Mural
Installation type	Interior

ENVIRONMENTAL CHARACTERISTIC

IP rating	IP20
RoHS Compliance	Conforme RoHS
Standards	- ROHS, REACH, SvHC
UV Resistance	No

ADDITIONAL INFORMATION

Product Packaging	Carton
Weight (Kg)	0.198