


48SMCSCAS

SC APC simplex single-mode fiber optic connector - Bag of 6

DESCRIPTION

Fiber optic connector with a blue composite body.
Connection by hot or cold bonding to loose-tube or tight-buffered cables.



ADVANTAGES

- UPC high precision ceramic ferrule
- 2mm & 3mm black boots included



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	48xMCyyyzz
Color	Green
Number of Optical Fibers	2
Optical Connector Type	SCA Simplex
Available Colors for Optical Connector	Green
Core Material	Composite
Gross Scanned Weight of the US (g/km)	0,04

ELECTRICAL CHARACTERISTICS

Optical Performance	Monomode
Insertion Loss	< 0,3dB
Return Loss	PC/UPC: > 25 dB / APC: > 55 dB

TRANSMISSION CHARACTERISTICS

Data Transmission Standard	EN 50173, ISO 11801-1 et TIA 568-3.D
Test Report	Non

MECHANICAL CHARACTERISTICS

Polishing Type	Multimode: PC / Monomode: UPC
----------------	-------------------------------

ENVIRONMENTAL CHARACTERISTIC

RoHS Compliance	Conforme RoHS
Standards	- ISO 11801 Ed3 - TIA 568-3.D - IEC 61754-4 - TIA/EIA 604.10
Component Standard	IEC 61754-20

ADDITIONAL INFORMATION

Product Packaging	Bag
Weight (Kg)	0.05