


BIFIBRESOM3

OS2 optical fiber optic dual cable LSZH sheath



DESCRIPTION

This OM3 optical cable is typically used for short distances: patch cords. OM3 multimode optical fiber meets and exceeds IEC*, ITU, and EIA/TIA specifications. The strands are natural-colored. Aramid fibers are positioned on the tight-buffered strands as strength members. An HFFR jacket is extruded over the strength members. The two simplex elements are assembled under a flexible LSZH jacket.



ADVANTAGES

- Good mechanical strength.
- Tightly woven cable for connection without fanouts.



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	BIFIBRESyyy
Color	Turquoise RAL 6027
Minimum diameter of the outer sheath (mm)	3.70 x 6.90
Nom. diameter of the outer sheath (mm)	3.80 x 7.00
Max. diameter of the outer sheath (mm)	3.90 x 7.10
Number of active tubes	2
Total number of tubes	2
Number of Optical Fibers	2
Number of Fibers per Tube	1
Sheath Type	LSZH

ELECTRICAL CHARACTERISTICS

Optical Performance	OM3
---------------------	-----

TRANSMISSION CHARACTERISTICS

Data Transmission Standard	ISO 11801-1 et TIA 568-3.D
----------------------------	----------------------------

MECHANICAL CHARACTERISTICS

Structure	Serrée
Max Short-Term Tensile Strength	500
Max Long-Term Tensile Strength	500 N
Bending Radius in Fixed Installation	20 x Ø ext
Bending Radius in Mobile Installation	20 x Ø ext
Max Short-Term Crush Resistance	1500
Max Long-Term Crush Resistance	1500 N/dm

ENVIRONMENTAL CHARACTERISTIC

CPR classification	Dca s2, d2, a2
Fire behaviour	IEC 60331-2
Smoke emission	IEC 61034-1 & -2
Gas emission	IEC 60754-2
UV Resistance	No
Component Standard	IEC 60794-1-2

ADDITIONAL INFORMATION

Product Packaging	Drum of 4000m
Weight (Kg)	34