

CAMTP12ALCDOM3

MTP cabled tray with 12 LC duplex OM3 adapters for CH1U fiber optic drawers

DESCRIPTION

6 or 12 LCD plug & play MTP tray for CH1U fiber optic drawers



ADVANTAGES

- Rapid installation
- LGX standard
- Plug and play solution



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	CAMTPxxALCDyyy
Color	Deep Black RAL 9005
Compatible optical connector	LC Duplex
Number of Optical Fibers	12
Number of Accepted Fibers	24
Optical Connector Type	LC Duplex
Dimensions (W x D x h)	28 x 103 x 130 mm
Containing Material	Tôle d' acier 15/10
Maximum Capacity Modularity	Fixation plug and play par bouton poussoir
Gross Scanned Weight of the US (g/km)	0,25

ELECTRICAL CHARACTERISTICS

Optical Performance	OM3
---------------------	-----

TRANSMISSION CHARACTERISTICS

Data Transmission Standard	EN 50173, ISO 11801 ED3, IEEE 802.3ae, TIA 568-C3
----------------------------	---

MECHANICAL CHARACTERISTICS

Installation type	Interior
-------------------	----------

ENVIRONMENTAL CHARACTERISTIC

IP rating	IP20
RoHS Compliance	Conforme RoHS
Standards	ISO 11801 ED2.2, EIA/TIA 568-C.3
Component Standard	IEC 61754-20, IEC 61754-7, TIA/568 EIA 604-5, TIA/EIA 455-21a

ADDITIONAL INFORMATION

Product Packaging	Unit
Weight (Kg)	0.25