

CORD6ASF01MSH

CAT6A S/FTP MMC RJ45 patch cord - 1 m



DESCRIPTION

The gray CORD6ASF01MSH Category 6A patch cord is used for patching IP equipment on the IT side and at the work area outlet. Its S/FTP shielding provides excellent electromagnetic immunity and enables it to achieve Class Ea link performance up to 500 MHz. Its LSZH jacket, available in various colors, facilitates identification in accordance with TIA-606A. Length: 1 m.



ADVANTAGES

- Class Ea link-certified
- Optimized NEXT
- 50 μ inch gold coating
- Excellent electromagnetic immunity thanks to S/FTP shielding
- LSZH sheath available in different colors for easy identification as per standard TIA-606A



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	CORD6ASFxxxxMSH
Color	Grey RAL 7035
Shielding type	S/FTP
End 2 - Number of connectors 2	1
Cord Length (m)	1m
Connector Format	Plug RJ45 Cat6A
Inserter Type	inserteur optimisé sur 2 niveaux
Contact Nature	Phosphore Bronze revêtement Or
Gross Scanned Weight of the US (g/km)	4,90

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	150V AC
PoE type	4PPoE

TRANSMISSION CHARACTERISTICS

Performance Category	Category 6A
Data Transmission Standard	EIA/TIA 568-C.2 Cat6A, EN 50173-1: 2011 Classe Ea, ISO 11801 Ed.3 Classe Ea

MECHANICAL CHARACTERISTICS

Bending Radius	8 x Ø externe
Insertion Cycle	750 cycles min / 1000 nom

ENVIRONMENTAL CHARACTERISTIC

Fire behaviour	IEC 60332-1, UL 94V0
IP rating	IP20
RoHS Compliance	Conforme RoHS
Operating Temperature	-20°C à +70°C
Component Standard	TIA 568-C.2 Cat6A

ADDITIONAL INFORMATION

System Warranty	25 years
Product Packaging	100% biodegradable bag
Weight (Kg)	0_01