

CORD6ASF03MSH

**CAT6A S/FTP MMC RJ45 patch cord - 3
m**



DESCRIPTION

CORD6ASFxMSH is a CAT6A S/FTP shielded patch cord from the MMC series. It is used for patching in a rack and/or the connection of IP equipment. It provides excellent electromagnetic immunity thanks to its shielding. Its LSZH sheath available in different colors facilitates identification as per standard TIA-606A. Length from 0.5m.



ADVANTAGES

- Class Ea link-certified
- Optimized NEXT
- 50 μ inch gold coating
- Excellent electromagnetic immunity thanks to S/FTP shielding
- LSZH sheath available in different colors for easy identification as per standard TIA-606A



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	CORD6ASFxxxxMSH
Color	Grey RAL 7035
Shielding type	S/FTP
End 2 - Number of connectors 2	1
Cord Length (m)	3m
Connector Format	Plug RJ45 Cat6A
Inserter Type	inserteur optimisé sur 2 niveaux
Contact Nature	Phosphore Bronze revêtement Or
Gross Scanned Weight of the US (g/km)	5,85

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	150V AC
PoE type	4PPoE

TRANSMISSION CHARACTERISTICS

Performance Category	Category 6A
Data Transmission Standard	EIA/TIA 568-C.2 Cat6A, EN 50173-1: 2011 Classe Ea, ISO 11801 Ed.3 Classe Ea

MECHANICAL CHARACTERISTICS

Bending Radius	8 x Ø externe
Insertion Cycle	750 cycles min / 1000 nom

ENVIRONMENTAL CHARACTERISTIC

Fire behaviour	IEC 60332-1, UL 94V0
IP rating	IP20
RoHS Compliance	Conforme RoHS
Operating Temperature	-20°C à +70°C
Component Standard	TIA 568-C.2 Cat6A

ADDITIONAL INFORMATION

System Warranty	25 years
Product Packaging	100% biodegradable bag
Weight (Kg)	0_03