

CORD6ASF0B03MSH

**CAT6A S/FTP AWG26 antibacterial
patch cord - 3 m**



DESCRIPTION

CAT6A S/FTP shielded RJ45 patch cord for patching in a rack and/or the connection of IP equipment. This patch cord is the perfect solution for aseptic environments such as agri-food or hospitals.

The Zero Bacteria cord meets the JIS Z280 anti-bacterial standard.



ADVANTAGES

- Antibacterial: JIS Z280
- Class Ea link-certified
- Optimized NEXT
- 50 μ inch gold coating
- Excellent electromagnetic immunity thanks to S/FTP shielding
- LSZH sheath available in different colors for easy identification as per standard TIA-606A



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	CORD6ASF0BxxMSH
Color	Signal White RAL 9003
Shielding type	S/FTP
End 2 - Number of connectors 2	1
Cord Length (m)	3m
Connector Format	Plug RJ45 Cat6A
Inserter Type	Plug sur 2 niveaux de raccordement. Optimisation du NEXT
Contact Nature	Phosphore Bronze plaqué or
Gross Scanned Weight of the US (g/km)	0,30

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	150V AC
PoE type	4PPoE

TRANSMISSION CHARACTERISTICS

Performance Category	Category 6A
Data Transmission Standard	EIA/TIA 568-C.2 Cat6A, EN 50173-1: 2011 Classe Ea, ISO / IEC 11801 Ed3 Class Ea

MECHANICAL CHARACTERISTICS

Bending Radius	8 x Ø exterieur
Insertion Cycle	750 cycles min / 1000 nom

ENVIRONMENTAL CHARACTERISTIC

Fire behaviour	IEC 60332-1, UL 94V0
IP rating	IP20
RoHS Compliance	Oui
Operating Temperature	-20°C to +70°C
Component Standard	TIA 568-C.2 Cat6A

ADDITIONAL INFORMATION

System Warranty	25 years
Product Packaging	100% biodegradable bag
Weight (Kg)	0_03