

CORD6ASFAG10MSH

CAT6A S/FTP RJ45 patch cord with straight/angled plug and LSZH sheath - 10 meters



DESCRIPTION

Cord comprising a CAT6A S/FTP AWG26 solid cable fitted with a straight RJ45 plug and an angled plug. Different lengths available. TIA 568 B cabling color code



ADVANTAGES

- Patch cord fitted with a straight RJ45 plug and an angled plug
- 50 µinch gold coating
- Excellent electromagnetic immunity thanks to S/FTP shielding
- LSZH sheath available in different colors for easy identification as per standard TIA-606A



CONSTRUCTION & TECHNICAL PERFORMANCE

| | |
|--------------------------------|----------------------------------|
| Product Type | CORD6ASFAGxxxxMSH |
| Color | Grey RAL 7035 |
| Shielding type | S/FTP |
| End 2 - Number of connectors 2 | 1 |
| Cord Length (m) | 10m |
| Connector Format | Plug RJ45 Cat6A |
| Inserter Type | inserteur optimisé sur 2 niveaux |

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|----------|
| Service Voltage (V) | 150 Veff |
| PoE type | 4PPoE |

TRANSMISSION CHARACTERISTICS

| | |
|----------------------------|--|
| Performance Category | Category 6A |
| Data Transmission Standard | EIA/TIA 568-C.2 Cat6A, EN 50173-1: 2011 Classe Ea, ISO 11801 Ed.3 Classe Ea |

MECHANICAL CHARACTERISTICS

| | |
|-----------------|--------------|
| Bending Radius | 8 x Øext |
| Insertion Cycle | ? 750 cycles |

ENVIRONMENTAL CHARACTERISTIC

| | |
|-----------------------|----------------------|
| Fire behaviour | IEC 60332-1, UL 94V0 |
| IP rating | IP20 |
| RoHS Compliance | Conforme RoHS |
| Operating Temperature | -20°C à +70°C |
| Component Standard | TIA 568-C.2 Cat6A |

ADDITIONAL INFORMATION

| | |
|-------------------|------------------------|
| System Warranty | 25 years |
| Product Packaging | 100% biodegradable bag |
| Weight (Kg) | 0_344 |