

CORD6AUL01MSH

CAT6A U/UTP LINK+ RJ45 patch cord -
1 m



DESCRIPTION

CORD6AULxMSH is a CAT6A U/UTP unshielded patch cord from the LINK+ series. It is used for patching in a rack and/or the connection of IP equipment. Length from 1 m.



ADVANTAGES

- Cat6A link-certified
- Optimized NEXT
- LSZH sheath



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	CORD6AULxxMSH
Color	Grey RAL 7035
Shielding type	U/UTP
End 2 - Number of connectors 2	1
Cord Length (m)	1m
Connector Format	Plug RJ45 Cat6A
Inserter Type	Optimisation du Next grâce à son plug à 2 niveaux
Contact Nature	Phosphore Bronze revêtement Or
Gross Scanned Weight of the US (g/km)	5,05

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	150V AC
---------------------	---------

TRANSMISSION CHARACTERISTICS

Performance Category	Category 6A
Data Transmission Standard	EIA/TIA 568-C.2 Cat6A, EN 50173-1: 2011 Classe Ea, ISO 11801 Ed.3 Classe Ea

MECHANICAL CHARACTERISTICS

Bending Radius	8 x Ø externe
Insertion Cycle	750 cycles min / 1000 nom

ENVIRONMENTAL CHARACTERISTIC

Fire behaviour	IEC 60332-1, UL 94V0
IP rating	IP20
RoHS Compliance	Conforme RoHS
Operating Temperature	-20°C à +70°C
Component Standard	TIA 568-C.2 Cat6A

ADDITIONAL INFORMATION

System Warranty	15 years
Product Packaging	100% biodegradable bag
Weight (Kg)	0_01