

CORD6AUL02MSH

**CAT6A U/UTP LINK+ RJ45 patch cord -
2 m**



DESCRIPTION

CORD6AULxMSH is a CAT6A U/UTP unshielded patch cord from the LINK+ series. It is used for patching in a rack and/or the connection of IP equipment.
Length from 1 m.



ADVANTAGES

- Cat6A link-certified
- Optimized NEXT
- LSZH sheath



CONSTRUCTION & TECHNICAL PERFORMANCE

| | |
|---------------------------------------|---|
| Product Type | CORD6AULxxMSH |
| Color | Grey RAL 7035 |
| Shielding type | U/UTP |
| End 2 - Number of connectors 2 | 1 |
| Cord Length (m) | 2m |
| Connector Format | Plug RJ45 Cat6A |
| Inserter Type | Optimisation du Next grace à son plug à 2 niveaux |
| Contact Nature | Phosphore Bronze revêtement Or |
| Gross Scanned Weight of the US (g/km) | 3,97 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|---------|
| Service Voltage (V) | 150V AC |
|---------------------|---------|

TRANSMISSION CHARACTERISTICS

| | |
|----------------------------|--|
| Performance Category | Category 6A |
| Data Transmission Standard | EIA/TIA 568-C.2 Cat6A, EN 50173-1: 2011 Classe Ea, ISO 11801 Ed.3 Classe Ea |

MECHANICAL CHARACTERISTICS

| | |
|-----------------|---------------------------|
| Bending Radius | 8 x Ø externe |
| Insertion Cycle | 750 cycles min / 1000 nom |

ENVIRONMENTAL CHARACTERISTIC

| | |
|-----------------------|----------------------|
| Fire behaviour | IEC 60332-1, UL 94V0 |
| IP rating | IP20 |
| RoHS Compliance | Conforme RoHS |
| Operating Temperature | -20°C à +70°C |
| Component Standard | TIA 568-C.2 Cat6A |

ADDITIONAL INFORMATION

| | |
|-------------------|------------------------|
| System Warranty | 15 years |
| Product Packaging | 100% biodegradable bag |
| Weight (Kg) | 0_02 |