



F5554SH1

CAT6A F/FTP 1x4P 555 MHz LSZH Dca
Cable Coil of 100m



DESCRIPTION

The CAT6A F/FTP F555xSHC cable is used in shielded cabling solutions for horizontal or vertical configurations. Its performance exceeds the limits imposed by CAT6A cabling standards up to 555 MHz thanks to an adapted construction and F/FTP shielding. The combination of overall and individual shielding provides high electromagnetic immunity (coupling attenuation > 85 dB). Declared Dca s2, d2, a2 according to CPR EN 50575.



ADVANTAGES

- Tested up to 555 MHz
- Very high electromagnetic immunity
- Available in high CPR level : up to B2ca



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	F555xSHyyyyyz
Core gauge	AWG23
Assembly type	Pairs
Shielding description	Aluminium polyester tape
Outer Sheath Material	LSZH
Color	Purple RAL 4001
Nom. diameter of the outer sheath (mm)	7.1
Ground drain presence	No
Shielding type	F/FTP
Insulation Color Code	Blue and White blue or White - Orange and White orange or White - Green and White green or White - Brown and White brown or White
Nominal insulation diameter (mm)	1,22

ELECTRICAL CHARACTERISTICS

Loop resistance	154
Minimum insulation resistance	> 5000 MΩ x km
Service Voltage (V)	<250Vdc
Linear electrical resistance (Ω/Km)	77
Mutual Capacity	< 45 pF
Capacity Imbalance	< 1600 pF/km

TRANSMISSION CHARACTERISTICS

Coupling attenuation (dB)	85
Delay skew	< 30
Unbalance resistance	< 2
Propagation speed (%)	79
Segregation Class	D
Performance Category	Category 6A
Data Transmission Standard	EIA/TIA 568-C.2 Cat6A, EN 50173-1: 2011 Classe Ea, ISO 11801 Ed.3 Classe Ea
Characteristic Impedance (Ohms)	100
Conductor/Shield Capacitance	1,6 nF/km
Conductor/Conductor Capacitance	45 nF/km

ENVIRONMENTAL CHARACTERISTIC

CPR classification	Dca s2, d2, a2
Fire behaviour	IEC 60332-1
Smoke emission	IEC 61034-1 & -2
Gas emission	IEC 60754-2
RoHS Compliance	Compliant with the RoHS directive
Component Standard	IEC 61156-5 Cat6A

ADDITIONAL INFORMATION

Product Packaging	Coil of 100m
Weight (Kg)	0.048

TRANSMISSION PERFORMANCE

FREQUENCY (Mhz)	INSERTION LOSS (dB/100M)		NEXT (dB/100M)		PSNEXT (dB/100M)		ACR-F (dB/100M)		PSACR-F (dB/100M)		RETURN LOSS (dB/100M)	
	Standard	Typical Value	Standard	Typical Value	Standard	Typical Value	Standard	Typical Value	Standard	Typical Value	Standard	Typical Value
4	-3,8	-3,5	-66,3	-100,0	-63,3	-97,0	-56,0	-106,4	-53,0	-103,4	-23,0	-27,9
10	-5,9	-5,4	-60,3	-106,7	-57,3	-103,7	-48,0	-107,6	-45,0	-104,6	-25,0	-30,3
16	-7,5	-6,8	-57,2	-110,3	-54,2	-107,3	-43,9	-107,5	-40,9	-104,5	-25,0	-33,7
20	-8,4	-7,6	-55,8	-108,1	-52,8	-105,1	-42,0	-108,5	-39,0	-105,5	-25,0	-30,2
31,25	-10,5	-9,7	-52,9	-110,2	-49,9	-107,2	-38,1	-102,5	-35,1	-99,5	-23,6	-30,6
62,5	-15,0	-14,0	-50,9	-103,5	-47,9	-100,5	-32,1	-98,3	-29,1	-95,3	-21,5	-31,1
100	-19,1	-17,8	-48,4	-101,3	-45,4	-98,3	-28,0	-97,2	-25,0	-94,2	-20,1	-41,3
125	-21,5	-20,0	-45,3	-99,0	-42,3	-96,0	-26,1	-95,0	-23,1	-92,0	-19,4	-37,0
155	-24,1	-22,1	-42,4	-98,5	-39,4	-95,5	-24,2	-93,0	-21,2	-90,0	-18,8	-33,0
200	-27,6	-25,4	-40,8	-97,9	-37,8	-94,9	-22,0	-90,1	-19,0	-87,1	-18,0	-30,1
250	-31,1	-27,5	-39,3	-98,0	-36,3	-95,0	-20,0	-86,0	-17,0	-83,0	-17,3	-30,0
300	-34,3	-31,4	-38,1	-99,2	-35,1	-96,2	-18,5	-83,1	-15,5	-80,1	-17,3	-29,7
350	-37,2	-34,2	-37,1	-95,0	-34,1	-92,0	-17,1	-83,0	-14,1	-80,0	-17,3	-28,0
400	-40,1	-36,3	-36,3	-92,0	-33,3	-89,0	-16,0	-83,2	-13,0	-80,2	-17,3	-27,1
450	-42,7	-39,0	-35,5	-91,0	-32,5	-88,0	-14,9	-77,0	-11,9	-74,0	-17,3	-27,5
500	-45,3	-40,9	-34,8	-90,5	-31,8	-87,5	-14,0	-74,9	-11,0	-71,9	-17,3	-27,9
555	N/A	-45,0	N/A	-90,0	N/A	-87,0	N/A	-71,0	N/A	-68,0	N/A	-25,0