

## FU1U48SCSLCD

**1U unequipped front panel for 48 SCS/  
LCD, screwless, for CH1U fiber optic  
drawers**

### **DESCRIPTION**

Removable front panels with 24 or 48 SCS, SCD, LCD or LCQ ports. They are intended to equip the CH1U sliding frame.

They are supplied unequipped, use 48xMTyyy adapters.

The F1U3MOD version is designed to accommodate 3 modules in LGX format.



### **ADVANTAGES**

- Rapid installation
- Modularity
- LGX standard



**CONSTRUCTION & TECHNICAL PERFORMANCE**

|                                       |                          |
|---------------------------------------|--------------------------|
| Product Type                          | FU1Uxxxxx                |
| Color                                 | Anthracite Grey RAL 7016 |
| Compatible optical connector          | LC Duplex, SC Simplex    |
| Number of Optical Fibers              | 48                       |
| Number of Accepted Fibers             | Jusqu'à 96 FO            |
| Optical Connector Type                | SC Simplex LC Duplex     |
| Dimensions (W x D x h)                | 44,45 x 482,6 x 10 mm    |
| Containing Material                   | Steel 12/10              |
| Gross Scanned Weight of the US (g/km) | 0,286                    |

**ELECTRICAL CHARACTERISTICS**

|                     |        |
|---------------------|--------|
| Optical Performance | Aucune |
|---------------------|--------|

**MECHANICAL CHARACTERISTICS**

|                   |          |
|-------------------|----------|
| Installation type | Interior |
|-------------------|----------|

**ENVIRONMENTAL CHARACTERISTIC**

|                 |                     |
|-----------------|---------------------|
| RoHS Compliance | RoHS compliant      |
| Standards       | - ROHS, REACH, SvHC |
| UV Resistance   | No                  |

**ADDITIONAL INFORMATION**

|                   |        |
|-------------------|--------|
| Product Packaging | Carton |
| Weight (Kg)       | 0.286  |