

IP55W12U60

**IP55 12U wall-mounted cabinet, 600mm depth**



## DESCRIPTION

IP55 cabinet in RAL 7035, robust and secure, equipped with a door fitted with lockable butterfly handles and a lock, an air filter and a double roof for natural ventilation. With its three cable glands, adjustable uprights and a 200 kg load capacity, it is ideal for demanding industrial environments.



## ADVANTAGES

- Load capacity 200 kg.
- Dust- and splash-proof (IP55).
- Intuitive wall-mounting system.
- Clean, neutral appearance to integrate into your environment.



**CONSTRUCTION & TECHNICAL PERFORMANCE**

|                                       |                          |
|---------------------------------------|--------------------------|
| Product Type                          | IP55WxxU60               |
| Color                                 | Light Grey RAL 7035      |
| Overall Dimensions (HxWxD)            | 676 x 600 x 600          |
| Usable Dimensions (HxWxD)             | 578 x 451 x (337-457)    |
| U Height                              | 12U                      |
| Rear Door Type                        | Single solid metal panel |
| Front Door Type                       | single full metal door   |
| Load Capacity                         | 200 Kg                   |
| Material Type                         | Steel                    |
| Gross Scanned Weight of the US (g/km) | 40                       |
| Product thickness                     | 1.2 mm                   |

**MECHANICAL CHARACTERISTICS**

|                           |                    |
|---------------------------|--------------------|
| Front Door Closing System | Sérrure à clé 4444 |
|---------------------------|--------------------|

**ENVIRONMENTAL CHARACTERISTIC**

|           |      |
|-----------|------|
| IP rating | IP55 |
|-----------|------|

**ADDITIONAL INFORMATION**

|                   |      |
|-------------------|------|
| Product Packaging | Unit |
| Weight (Kg)       | 38.5 |