

IP55W16U60

IP55 16U wall-mounted cabinet, 600mm depth



DESCRIPTION

IP55 cabinet in RAL 7035, robust and secure, equipped with a door fitted with lockable butterfly handles and a lock, an air filter and a double roof for natural ventilation. With its three cable glands, adjustable uprights and a 200 kg load capacity, it is ideal for demanding industrial environments.



ADVANTAGES

- Load capacity 200 kg.
- Dust- and splash-proof (IP55).
- Intuitive wall-mounting system.
- Clean, neutral appearance to integrate into your environment.



Updated: 1/02/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	IP55WxxU60
Color	Light Grey RAL 7035
Overall Dimensions (HxWxD)	854 x 600 x 600
Usable Dimensions (HxWxD)	755.8 x 451 x (337-457)
U Height	16U
Rear Door Type	single full metal door
Front Door Type	single full metal door
Load Capacity	200 Kg
Material Type	Steel
Gross Scanned Weight of the US (g/km)	46
Product thickness	1.2 mm

MECHANICAL CHARACTERISTICS

Front Door Closing System	serrure à clé 4444
---------------------------	--------------------

ENVIRONMENTAL CHARACTERISTIC

IP rating	IP55
-----------	------

ADDITIONAL INFORMATION

Product Packaging	Unit
Weight (Kg)	44.5