

LK2466

19" cabling bay - 600 x 600 - 24U - Link+ range



DESCRIPTION

The 19" bays of the LK Range, equipped with a glass front door, are the starting point for the cabling infrastructure. The load capacity of 700 kg is ensured by its rigid mechanically screwed structure.



ADVANTAGES

- Load capacity of 700 kg
- 4 numbered 19"" uprights
- Secure front door closure with key (5333) • Single side and rear panel up to 27U and Double side and rear panels from 42U: Simple installation/handling
- Mechanically screwed structure



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	LKxx6z
Color	Anthracite Grey RAL 7016
Overall Dimensions (HxWxD)	1217x600x600
Usable Dimensions (HxWxD)	1127x451x508
U Height	24U
Rear Door Type	Single solid metal panel
Front Door Type	single glass door
Load Capacity	700 kg
Material Type	Steel
Gross Scanned Weight of the US (g/km)	45
Product thickness	1.2 mm

MECHANICAL CHARACTERISTICS

Front Door Closing System	Key lock 5333
---------------------------	---------------

ENVIRONMENTAL CHARACTERISTIC

IP rating	IP20
-----------	------

ADDITIONAL INFORMATION

Product Diagram	Sh_ma_baies_LKxx6y_dimutiles
Product Packaging	Unit
Weight (Kg)	40.5