

LK4266

**19" cabling bay - 600 x 600 - 42U - Link+ range**



## DESCRIPTION

The 19" racks of the LK Range, equipped with a glazed front door, are the starting point for cabling infrastructures. The 700 kg load capacity is ensured by its rigid, bolted mechanical structure.



## ADVANTAGES

- Load capacity of 700 kg
- 4 numbered 19" uprights
- Secure front door closure with key (5333) • Single side and rear panel up to 27U and Double side and rear panels from 42U: Simple installation/handling
- Mechanically screwed structure



Updated: 1/02/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

**CONSTRUCTION & TECHNICAL PERFORMANCE**

Product Type	LKxx6z
Color	Anthracite Grey RAL 7016
Overall Dimensions (HxWxD)	2017 x 600 x 600
Usable Dimensions (HxWxD)	1927 x 451 x 508
U Height	42U
Rear Door Type	Double solid metal panel
Front Door Type	single glass door
Load Capacity	700 kg
Material Type	Steel
Gross Scanned Weight of the US (g/km)	78
Product thickness	1.2 mm

**MECHANICAL CHARACTERISTICS**

Front Door Closing System	Key lock 5333
---------------------------	---------------

**ENVIRONMENTAL CHARACTERISTIC**

IP rating	IP20
-----------	------

**ADDITIONAL INFORMATION**

Product Diagram	Schema_Baies_portes_LK4266
Product Packaging	Unit
Weight (Kg)	73.5

## Additional Information

