

LK42810

**19" cabling bay - 800 x 1000 - 42U -
Link+ range**



DESCRIPTION

The 19" bays of the LK Range, equipped with a double glass front door, are the starting point for the cabling infrastructure. The load capacity of 700 kg is ensured by its rigid mechanically screwed structure.



ADVANTAGES

- Load capacity of 700 kg
- 4 numbered 19"" uprights
- Closing of the double front door, secured by key (4444)
- Single side and rear panel up to 27U and Double side and rear panels from 42U: Simple installation/handling
- Mechanically screwed structure



CONSTRUCTION & TECHNICAL PERFORMANCE

| | |
|---------------------------------------|--------------------------|
| Product Type | LKxx8z |
| Color | Anthracite Grey RAL 7016 |
| Overall Dimensions (HxWxD) | 2017 x 800 x 1000 |
| Usable Dimensions (HxWxD) | 1927 x 451 x 908 |
| U Height | 42U |
| Rear Door Type | Double solid metal panel |
| Front Door Type | double glazed door |
| Load Capacity | 700 kg |
| Material Type | Steel |
| Gross Scanned Weight of the US (g/km) | 111 |
| Product thickness | 1.2 mm |

MECHANICAL CHARACTERISTICS

| | |
|---------------------------|------------------------------|
| Front Door Closing System | 2 key locks, top and bottom. |
|---------------------------|------------------------------|

ENVIRONMENTAL CHARACTERISTIC

| | |
|-----------|------|
| IP rating | IP20 |
|-----------|------|

ADDITIONAL INFORMATION

| | |
|-------------------|-----------------------------|
| Product Diagram | Schema_Baies_portes_LK42810 |
| Product Packaging | Unit |
| Weight (Kg) | 102.5 |

Additional Information

