

LK4286

19" cabling bay - 800 x 600 - 42U – Link+ range



DESCRIPTION

The 19" bays of the LK Range, equipped with a double glass front door, are the starting point for the cabling infrastructure. The load capacity of 700 kg is ensured by its rigid mechanically screwed structure.



ADVANTAGES

- Load capacity of 700 kg
- 4 numbered 19" uprights
- Closing of the double front door, secured by key (4444)
- Single side and rear panel up to 27U and Double side and rear panels from 42U: Simple installation/handling
- Mechanically screwed structure



Updated: 1/02/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	LKxx8z
Color	Anthracite Grey RAL 7016
Overall Dimensions (HxWxD)	2017 x 800 x 600
Usable Dimensions (HxWxD)	1927 x 451 x 508
U Height	42U
Rear Door Type	Double solid metal panel
Front Door Type	double glazed door
Load Capacity	700 kg
Material Type	Steel
Gross Scanned Weight of the US (g/km)	98
Product thickness	1.2 mm

MECHANICAL CHARACTERISTICS

Front Door Closing System	2 key locks, top and bottom.
---------------------------	------------------------------

ENVIRONMENTAL CHARACTERISTIC

IP rating	IP20
-----------	------

ADDITIONAL INFORMATION

Product Diagram	Sh_ma_baies_LKxx8y_dimutiles
Product Packaging	Unit
Weight (Kg)	91.5