

TC1U12ASCDOM3

**1U 19" fiber optic drawer equipped with
12 SCD OM3 adapters**



DESCRIPTION

This 1U 19" steel fiber optic drawer is equipped with a sliding tray angled at 45° when it is opened, to make implementation or maintenance easier, while ensuring IP30 protection once closed.

The TC1UxxAyyyzzz drawer is available in different versions: 6 or 12 adapters in LC duplex or SC duplex, multi-mode or single-mode.



ADVANTAGES

- Time saving on installation: adapters already installed
- Optimized depth: easy coiling management
- Easy to implement
- Easy opening / closing, via 2 clips at each end of the drawer



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	TC1UxxAyyyzzz
Color	Anthracite Grey RAL 7016
Compatible optical connector	SC Duplex
Number of Optical Fibers	12
U Height	1U
Optical Connector Type	SC Duplex
Number of Insertions	1000
Inch Format	19"
Dimensions (W x D x h)	44 x 482,6 x 245 mm
Maximum Capacity Modularity	Tiroir coulissant, système d'ouverture - fermeture par clip
Gross Scanned Weight of the US (g/km)	2,20

ELECTRICAL CHARACTERISTICS

Optical Performance	OM3
---------------------	-----

TRANSMISSION CHARACTERISTICS

Data Transmission Standard	EN 50173, ISO 11801 ED3, TIA 568-C3
----------------------------	-------------------------------------

MECHANICAL CHARACTERISTICS

Optical mounting type	Rackable 19"
Installation type	Interior

ENVIRONMENTAL CHARACTERISTIC

IP rating	IP30
RoHS Compliance	Conforme RoHS
Standards	- TIA/EIA 568 C.3 - ISO/IEC 11801 Ed3 - EN 50173 - TIA/568 EIA 604-5 - TIA/EIA 455-21a - ROHS, REACH, SvHC
Component Standard	TIA/568 EIA 604-5, TIA/EIA 455-21a

ADDITIONAL INFORMATION

Product Packaging	cardboard of 1
Weight (Kg)	2.2