

TC1U12PLCDOM5

1U 19" sliding fiber optic drawer with 6 LCD adapters and 12 OM5 pigtails



DESCRIPTION

1U 19" sliding optical drawer with 6 multimode LCD adapters and 12 OM5 pigtails



ADVANTAGES

- Time saving on installation: adapters and pigtails already installed and connected
- Adapters and pigtails tested after assembly operations
- Easy to implement
- Easy opening / closing, via 2 clips at each end of the drawer



CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	TC1UxxPyyzzz
Color	Anthracite Grey RAL 7016
Compatible optical connector	LC Duplex
Number of Optical Fibers	12
U Height	1U
Optical Connector Type	LC Duplex
Number of Insertions	1000
Inch Format	19"
Dimensions (W x D x h)	44,45 x 482,6 x 245 mm
Maximum Capacity Modularity	Sliding drawer, clip opening and closing system
Gross Scanned Weight of the US (g/km)	3,20

ELECTRICAL CHARACTERISTICS

Optical Performance	OM5
---------------------	-----

TRANSMISSION CHARACTERISTICS

Data Transmission Standard	EN 50173, ISO 11801 ED3, TIA 568-C3
----------------------------	-------------------------------------

MECHANICAL CHARACTERISTICS

Optical mounting type	Rackable 19"
Installation type	Interior

ENVIRONMENTAL CHARACTERISTIC

IP rating	IP30
RoHS Compliance	RoHS compliant
Standards	<ul style="list-style-type: none"> - TIA/EIA 568 C.3 - ISO/IEC 11801 Ed3 - EN 50173 - IEC 61754 - TIA/568 EIA 604-5 - TIA/EIA 455-21a - ROHS, REACH, SvHC
Component Standard	TIA/568 EIA 604-5, TIA/EIA 455-21a

ADDITIONAL INFORMATION

Product Packaging	cardboard of 1
Weight (Kg)	2.5