

TC1U12PSCDOS2

1U 19" sliding fiber optic drawer with 6 SCD adapters and 12 OS2 pigtails



## DESCRIPTION

1U 19" sliding optical drawer with 6 monomode SCD adapters and 12 OS2 pigtails



## ADVANTAGES

- Time saving on installation: adapters and pigtails already installed and connected
- Adapters and pigtails tested after assembly operations
- Easy to implement
- Easy opening / closing, via 2 clips at each end of the drawer



Updated: 1/02/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

**CONSTRUCTION & TECHNICAL PERFORMANCE**

Product Type	TC1UxxPyzzzz
Color	Anthracite Grey RAL 7016
Compatible optical connector	SC Duplex
Number of Optical Fibers	12
U Height	1U
Optical Connector Type	SC Duplex
Number of Insertions	1000
Inch Format	19"
Dimensions (W x D x h)	44 x 482,6 x 245 mm
Maximum Capacity Modularity	Sliding drawer, clip opening and closing system
Gross Scanned Weight of the US (g/km)	2,50

**ELECTRICAL CHARACTERISTICS**

Optical Performance	OS2
---------------------	-----

**TRANSMISSION CHARACTERISTICS**

Data Transmission Standard	EN 50173, ISO 11801 ED3, TIA 568-C3
----------------------------	-------------------------------------

**MECHANICAL CHARACTERISTICS**

Optical mounting type	Rackable 19"
Installation type	Interior

**ENVIRONMENTAL CHARACTERISTIC**

IP rating	IP30
RoHS Compliance	RoHS compliant
Standards	<ul style="list-style-type: none"><li>- TIA/EIA 568 C.3</li><li>- ISO/IEC 11801 Ed3</li><li>- EN 50173</li><li>- IEC 61754</li><li>- TIA/568 EIA 604-5</li><li>- TIA/EIA 455-21a</li><li>- ROHS, REACH, SvHC</li></ul>
Component Standard	TIA/568 EIA 604-5, TIA/EIA 455-21a

**ADDITIONAL INFORMATION**

Product Packaging	cardboard of 1
Weight (Kg)	2.5