

TC1U24SCSLCD

**1U 19" sliding fiber optic drawer for 24 SCS/LCD**

## DESCRIPTION

The 19" TC1Ux fiber optic drawer makes access to and maintenance of indoor applications easier, while ensuring IP30 protection. It saves time for technicians and is available with an SC or LC connection. It is a secure transition point for linking single-mode application connections or in multi-mode.



## ADVANTAGES

- Optimized depth: Easy coiling management
- Easy to implement
- Easy opening / closing, via 2 clips at each end of the drawer



**CONSTRUCTION & TECHNICAL PERFORMANCE**

|                                       |                                                 |
|---------------------------------------|-------------------------------------------------|
| Product Type                          | TC1Uxxxxx                                       |
| Color                                 | Anthracite Grey RAL 7016                        |
| Compatible optical connector          | LC Duplex, SC Simplex                           |
| Number of Optical Fibers              | 24                                              |
| U Height                              | 1U                                              |
| Number of Accepted Fibers             | Jusqu'à 48 FO                                   |
| Optical Connector Type                | SC Simplex LC Duplex                            |
| Inch Format                           | 19"                                             |
| Dimensions (W x D x h)                | 44 x 482,6 x 245 mm                             |
| Maximum Capacity Modularity           | Sliding drawer, clip opening and closing system |
| Gross Scanned Weight of the US (g/km) | 2,20                                            |

**ELECTRICAL CHARACTERISTICS**

|                     |        |
|---------------------|--------|
| Optical Performance | Aucune |
|---------------------|--------|

**MECHANICAL CHARACTERISTICS**

|                       |              |
|-----------------------|--------------|
| Optical mounting type | Rackable 19" |
| Installation type     | Interior     |

**ENVIRONMENTAL CHARACTERISTIC**

|                 |                     |
|-----------------|---------------------|
| IP rating       | IP30                |
| RoHS Compliance | RoHS compliant      |
| Standards       | - ROHS, REACH, SvHC |
| UV Resistance   | No                  |

**ADDITIONAL INFORMATION**

|                   |        |
|-------------------|--------|
| Product Packaging | Carton |
| Weight (Kg)       | 2.2    |